

COPPER BONDED EARTH RODS / GROUND RODS



File No. E339698

TRADE NAME	SIZE DETAILS				PART NO.	LISTING
	THREAD SIZE (A)	SHANK DIA (B)	LENGTH (C)	Cu THICKNESS AT ANY POINT		
5/8" x 8 Feet	Unthreaded	14.2mm	8 Feet	254µM Min.	C-5808BU	
5/8" x 8 Feet	Unthreaded	14.2mm	8 Feet	330µM Min.	C-5808BUR	
5/8" x 10 Feet	5/8"	14.2mm	10 Feet	254µM Min.	C-5810BT	
5/8" x 10 Feet	5/8"	14.2mm	10 Feet	330µM Min.	C-5810BTR	
5/8" x 10 Feet	Unthreaded	14.2mm	10 Feet	254µM Min.	C-5810BU	
5/8" x 10 Feet	Unthreaded	14.2mm	10 Feet	330µM Min.	C-5810BUR	
5/8" x 12 Feet	5/8"	14.2mm	12 Feet	254µM Min.	C-5812BT	
5/8" x 12 Feet	Unthreaded	14.2mm	12 Feet	254µM Min.	C-5812BU	
3/4" x 4 Feet	3/4"	17.2mm	4 Feet	254µM Min.	C-3404BT	
3/4" x 4 Feet	Unthreaded	17.2mm	4 Feet	254µM Min.	C-3404BU	
3/4" x 5 Feet	3/4"	17.2mm	5 Feet	254µM Min.	C-3405BT	
3/4" x 5 Feet	Unthreaded	17.2mm	5 Feet	254µM Min.	C-3405BU	
3/4" x 6 Feet	3/4"	17.2mm	6 Feet	254µM Min.	C-3406BT	
3/4" x 6 Feet	Unthreaded	17.2mm	6 Feet	254µM Min.	C-3406BU	
3/4" x 8 Feet	3/4"	17.2mm	8 Feet	254µM Min.	C-3408BT	
3/4" x 8 Feet	Unthreaded	17.2mm	8 Feet	254µM Min.	C-3408BU	
3/4" x 10 Feet	3/4"	17.2mm	10 Feet	254µM Min.	C-3410BT	
3/4" x 10 Feet	Unthreaded	17.2mm	10 Feet	254µM Min.	C-3410BU	
3/4" x 12 Feet	3/4"	17.2mm	12 Feet	254µM Min.	C-3412BT	
3/4" x 12 Feet	Unthreaded	17.2mm	12 Feet	254µM Min.	C-3412BU	
1" x 8 Feet	1"	23mm	8 Feet	254µM Min.	C-0108BT	
1" x 8 Feet	Unthreaded	23mm	8 Feet	254µM Min.	C-0108BU	
1" x 10 Feet	1"	23mm	10 Feet	254µM Min.	C-0110BT	
1" x 10 Feet	Unthreaded	23mm	10 Feet	254µM Min.	C-0110BU	

* Rods with special diameters, different lengths are available on request.

* Threading mentioned above are UNC Threads. BSW or Metric Threads are also available on request.

* Copper Plating Thickness for the above or special sizes can be maintained in the range of 50µM and up to 500µM for special applications on request.

