



A RANGE OF
**CUTTING
CRIMPING**
MULTI PURPOSE
**HYDRAULIC
TOOLS FOR**
ELECTRICAL
INDUSTRY





INTRODUCTION

Our product catalogue contains a wide range of cutting, crimping and other multipurpose hydraulic tools which are being generally used in the Electrical Industry. A brief technical write up is here to ensure a **PERFECT CRIMPED JOINT** always as a **JOINT** can be considered as the **NERVE CENTRE** of an Electrical System.

The most commonly used Crimping methods are Indent style and Hexagonal type. Indent style crimping method is usually used for crimping fine stranded and compacted conductors. This style of crimp yields great pullout resistance and good electrical performance when correctly made with a properly sized tool for the cable and connector. As the strands are formed tightly together inside the connector, nearly all air gaps are removed from the conductor. However, it is more difficult to check if an indent style crimp has been properly made compared to hex-style crimps.

Hexagonal type the most common type of crimp, create strong mechanical connections. The advantage of this style crimp is that force is applied consistently from all directions over a larger area during crimping, preventing any damage to the conductors. This style crimp is an industry standard for aluminum and copper cables up to 1000mm². Hex-style crimps yield superior electrical performance in addition to great pullout strength.




Indent Crimp Profile




Hexagonal Crimp Profile

QUICK REFERENCE WHICH TELLS YOU THE CRIMP QUALITY



Acceptable



Not Acceptable-under Crimped



Not Acceptable-over Crimped



HYDRAULIC HAND PUMP

Model No.
CT-HC-700B



Length: 600 mm

Weight: 10 kgs

Technical Data :

Max Pressure : 700 bar

Oil Required : 750 cc

Oil Delivery : 12 cc at low pressure &
2.3 cc at high pressure

Features :

Can be operated in any direction.
Cartridge valve installed for pressure cut-off.

2 stage pumping action.

CUT IT

CRIMP-IT

FORCEIT



HYDRAULIC HAND PUMP

Model No.
CT-HP-700B-EC



Length: 600 mm

Weight: 16 kgs

Technical Data :

Max Pressure : 700 bar

Oil Required : 3 Ltr.

Oil Delivery : 12 cc at low pressure &
3 cc at high pressure

Features :

Suitable for extra long jack applications.

Catridge valve installed for pressure cut-off.

2 stage pumping action.

CUT IT

CRIMP-IT

FORCE IT